


PRODUCT DESCRIPTION

- » Ideal for adjusting the length of cutting punches and cutting dies in stamping dies
- » Simplifies the adjustment of slide units in injection moulds
- » Helps align the workpieces on surface grinding and milling machines



MATERIAL

- » 1.1274

| s Tol. +/- | HRC | s | b | l | Pcs./PU | No. | EUR |
|------------|-----|------|----|-----|---------|-----------------------|-----|
| 0.003 | 57 | 0.03 | 50 | 300 | 10 | V 56062/0,03/ 50x 300 | <> |
| 0.003 | 57 | 0.04 | 50 | 300 | 10 | V 56062/0,04/ 50x 300 | <> |
| 0.003 | 57 | 0.05 | 50 | 300 | 10 | V 56062/0,05/ 50x 300 | <> |
| 0.003 | 57 | 0.06 | 50 | 300 | 10 | V 56062/0,06/ 50x 300 | <> |
| 0.004 | 57 | 0.07 | 50 | 300 | 10 | V 56062/0,07/ 50x 300 | <> |
| 0.004 | 57 | 0.08 | 50 | 300 | 10 | V 56062/0,08/ 50x 300 | <> |
| 0.004 | 57 | 0.09 | 50 | 300 | 10 | V 56062/0,09/ 50x 300 | <> |
| 0.004 | 57 | 0.1 | 50 | 300 | 10 | V 56062/0,10/ 50x 300 | <> |
| 0.004 | 57 | 0.12 | 50 | 300 | 10 | V 56062/0,12/ 50x 300 | <> |
| 0.005 | 55 | 0.15 | 50 | 300 | 10 | V 56062/0,15/ 50x 300 | <> |
| 0.006 | 54 | 0.2 | 50 | 300 | 10 | V 56062/0,20/ 50x 300 | <> |

| s Tol. +/- | HRC | s | b | l | Pcs./PU | No. | EUR |
|------------|-----|------|----|-----|---------|-----------------------|-----|
| 0.007 | 54 | 0.25 | 50 | 300 | 10 | V 56062/0,25/ 50x 300 | <> |
| 0.007 | 54 | 0.3 | 50 | 300 | 10 | V 56062/0,30/ 50x 300 | <> |
| 0.008 | 54 | 0.35 | 50 | 300 | 10 | V 56062/0,35/ 50x 300 | <> |
| 0.009 | 52 | 0.4 | 50 | 300 | 10 | V 56062/0,40/ 50x 300 | <> |
| 0.009 | 52 | 0.45 | 50 | 300 | 10 | V 56062/0,45/ 50x 300 | <> |
| 0.01 | 52 | 0.5 | 50 | 300 | 10 | V 56062/0,50/ 50x 300 | <> |
| 0.01 | 49 | 0.6 | 50 | 300 | 10 | V 56062/0,60/ 50x 300 | <> |
| 0.012 | 49 | 0.7 | 50 | 300 | 10 | V 56062/0,70/ 50x 300 | <> |
| 0.013 | 49 | 0.8 | 50 | 300 | 10 | V 56062/0,80/ 50x 300 | <> |
| 0.013 | 49 | 0.9 | 50 | 300 | 10 | V 56062/0,90/ 50x 300 | <> |
| 0.018 | 49 | 1 | 50 | 300 | 10 | V 56062/1,00/ 50x 300 | <> |